



FEATURES

- Best picture quality (in combination with Digital LCD monitor)
- High resolution CMOS camera (1.23Mega pixels)
- 1/3.2” Color CMOS high resolution image sensor
- IP68 Waterproof Rating
- Diagonal 130° Viewing
- Adjustable Mirror/Normal Image
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone
- Built-in IR LED’s
- Temp. -30°C ~ 80°C
- Vibration resistant
- Aluminum die-cast housing
- Anti-corrosive, chromate coating
- Waterproof screw type connector (IP68), 4-pin mini-DIN.
- E-mark

Specifications

Image Sensor	1/3.2” CMOS Sensor (Exmor)
Scanning System	CVBS -PAL 1.23Mega pixels
Resolution	750 TV Lines
S/N ratio	Better than 50dB (at AGC off)
Minimum Illumination	0 lux (IR LED’s on)
Power supply	DC 9 ~ 24V
Power Consumption	DC 9V, 170mA DC 24V, 60mA
Operating Temperature	-30°C to +80°C
Field of View angle	130° (Diagonal), 110° (Horizontal), 81° (Vertical)
Dimension	72(W) x 77(H) x 50(D) mm
Weight	205g (total weight incl. bracket & sunvisor: 312g)



FEATURES

- Best picture quality (in combination with Digital LCD monitor)
- High resolution CMOS camera (1.23Mega pixels)
- 1/3.2" Color CMOS high resolution image sensor
- IP68 Waterproof Rating
- Diagonal 130° Viewing
- Adjustable Mirror/Normal Image
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone
- Built-in IR LED's
- Temp. -30°C ~ 80°C
- Vibration resistant
- Aluminum die-cast housing
- Anti-corrosive, chromate coating
- Waterproof screw type connector (IP68), 4-pin mini-DIN.
- E-mark

Specifications

Image Sensor	1/3.2" CMOS Sensor (Exmor)
Scanning System	CVBS - NTSC 1.23Mega pixels
Resolution	750 TV Lines
S/N ratio	Better than 50dB (at AGC off)
Minimum Illumination	0 lux (IR LED's on)
Power supply	DC 9 ~ 24V
Power Consumption	DC 9V, 170mA DC 24V, 60mA
Operating Temperature	-30°C to +80°C
Field of View angle	130° (Diagonal), 110° (Horizontal), 81° (Vertical)
Dimension	72(W) x 77(H) x 50(D) mm
Weight	205g (total weight incl. bracket & sunvisor: 312g)